

#### APPLICATIONS

Powerchairs / home mobility equipment  
Scooters, 3- and 4 wheels  
Toys for children  
Lifts (stairs / bathrooms)  
Personal Carriers  
Utility Vehicles

#### SPECIFICATIONS

Nominal Voltage		12V
Nominal capacity @20 hour rate		130Ah
Capacity at 25°C	10 hour rate	120Ah
	5 hour rate	110Ah
	1 hour rate	84Ah
Shelf time @20°C up to 70%	in months	9
Internal resistance (at 1 KHz)		approx. 4,8mΩ
Operating temperature for (dis)charge		-15°C to + 40°C

#### DIMENSIONS


Dimensions LxWxH (T) in mm	330x171x214 (214)
Weight	34kg (±2%)
Separator	AGM, <b>Advanced Glass Matt</b>
Case and cover	ABS (UL94-V0 optional)
Terminal	M8 Bolt
Torque setting (recommended)	M8 (copper): 10 Nm
Maximum allowable torque value	M8 (copper): 12 Nm

#### CHARGING

Charging Voltage cycle use 14,4 to 15 Volt  
Float charge Voltage 13,5 to 13,8 Volt  
Charging current, minimum 15A - maximum 20A


#### CYCLE LIFE

To maximize the cycle life of the battery, we recommend to charge the battery fully after use. The total life of the battery, is very dependant on the correct charge and depth of discharge per cycle.



#### BATTERY LIFE UNDER CYCLIC USE

Tested in conformance to the BCI testing method



\* Cycle life is measured with a discharge current 0,2C, charged 16h and rest capacity of 2/3 Cn