



MTG 145-12

12V-150Ah - GEL Battery

APPLICATIONS

- Electric Vehicles (EV)
- Home Mobility Equipment (HME)
- Cleaning Equipment
- Solar Applications
- All deep cycle applications

SPECIFICATIONS

Nominal Voltage		12V
80% DoD Voltage Cutoff		11.4V (1,90 VPC)
Nominal capacity @20 hour rate	1.75VPC	150Ah
Capacity at 25°C	Capacity at 25°C 10 hour rate	146Ah
	5 hour rate	129Ah
Shelf time @20°C up to 70%	in months	12
Self discharge	per month	<3% (20°C)
Operating temperature for (dis)charge		-10°C to + 50°C

DIMENSIONS

Dimensions LxWxH (T) in mm	512 x 222 x 221 (241)
Weight	50kg (±2%)
Terminal	SAE / A-pole
Terminal torque setting	n.a.
BCI-Group	4D

CHARGING PROFILE (25°C in cyclic application)


IU Charging	I =	Min 16Amp / max. 23Amp
	U =	2.43 per cell
IUI Charging	I ¹ =	Min. 16Amp / max. 23Amp
	U =	2.38V per cell
	I ² =	Max. 2Amp (for max. 4 hours to max. 2.65V per cell)
Float-Voltage	U-float =	2,30VPC
Temperature compensation is 3 Mv per degree°C up or down from 25°C		

CYCLE LIFE

To maximize the cycle life of the battery, we recommend to charge the battery fully after use. The total life of the battery, is very dependant on the correct charge and depth of discharge per cycle.

FEATURES

- Maintenance-free bloc batteries in Gel technology
- Stable high current performance for extreme conditions
- High-class patented safety valve
- Valve-regulated lead-acid battery filled with thixotropic gel
- Classified as a non-spillable battery
- 700 cycles according to IEC 61427 / 60896-21/22



GEL Cycle Life vs Depth of Discharge at +25°C
Based on IEC 254-1

